

Product Name :
 Planomiller Machine

Product Code :
 sp0002



Description :

Planomiller Machine

Technical Specification :

Planomiller Machine.

Spindle Nose	ISO 50	ISO 50	ISO 50	ISO 50
Spindle Speeds	6	8	8	12
Speed Range	45-300 RPM	45-400 RPM	45-400 RPM	20-450 RPM
Drill Stroke	100 mm	125 mm	150 mm	180 mm
Spindle Dia	85 mm	95 mm	110 mm	125 mm

SPECIFICATION OF PLANOMILLER MACHINES

Specifications		AY-1	AY-2	BY-1	BY-2	DY-1	DY-2
Table Stroke	Meters	1.8	2.4	3.6	4.8	5.4	6
Planning	mm	1200	120 C	1500	1500	1800	1800

Width		(can be up to 1500)		(can be up to 2100)		(can be up to 2400)	
Planning	mm	1200	1200	1500	1500	1800-2400	1800-2400
Height under Cross Rail		(can be up to 1500)		(can be up to 2100)			
Length of Bed	mm	2700	3600	5400	7500	8400	9300
Height of Bed	mm	600	600	650	650	700	700
Centre to Centre Width of Bed	mm	650	650	700	700	800	800
		(can be up to 700)		(can be up to 800)		(can be up to 950)	
Width of Table	mm	975	975	1050	1050	1200	1200
		(can be up to 1050)		(can be up to 1200)		(can be up to 1750)	
Thickness of Table	mm	175	175	225	225	250	250
Face of Pillar	mm	300	300	350	350	400	400
Face of Cross Rail	mm	400	400	500	500	600	
Speed Cutting & Return as Planner	mts/mm	15/23	15/23	15/23	15/23	13/19	13/19
Table Feed Range as Piano Miller	mm/min.	(Twenty Five to Two Hundred Fifty)					
Driving Unit	mm	(Screw Nut Drive)			(Worm and Half Nut Type Rack)		
Approx Weight	tons	12	14	22	26	40	45

© LAB ENGINEERING

Elab Engineering Equipments Manufacturers

