

Product Name :
 Pedestal Grinder With Coolant & Fittings

Product Code :
 gm0014



Description :

Pedestal Grinder With Coolant & Fittings

Technical Specification :

WHEEL FLANGES - Wheel flanges are of balanced design, the inner pair keyed to the spindle for positive drive for 18" to 40 " grinders. TOOL RESTS - These are adjustable both in horizontal and vertical positions for allowing maximum wear and tear of the wheels. DRIVE - Through V-belts to the spindle by an Electric Motor. Two speeds are provided to maintain peripheral speeds when the wheels wear out. ELECTRICALS - 400/440 volts 3 phase 50 cycles ISI Mark Electric Motor with LT/LK/BETEX Push button starter direct on line with overload, undervoltage. SPECIAL ACCESSORIES AT EXTRA COST: Coolant equipment, Twist drill Grinding Attachment, Dust Exhaust Equipment, Machine Light, Water Pot and Foundation Nuts & Bolts.

Dia	250	300	350	400	450	500	600	750	1000
Width	25	38	50	50	76	76	76	101	101
Bore	25.4	25.4	38.1	38.1	152.4	152.4	203.2	304.8	406.4
Centre Distance	600	625	650	765	840	840	920	1025	1500
SPINDLE									
Centre height	910	910	910	860	860	860	860	810	810
R.P.M.	2800	1500	1500	1500	1500	1450	1200	950	500

ELECTRIC MOTOR

H.P. 3 Phase

1

2

2

3

5

5

7.5

10

20

 **LAB ENGINEERING**

Elab Engineering Equipments Manufacturers