

Product Name :
Universal Edging & Bending Machine

Product Code :
sc0006



Description :

Universal Edging & Bending Machine

Technical Specification :

Universal Edging & Bending Machine.

Universal Combination bending brakes represent a modern departure from the old conventional hand brake design. They are not limited to straight bending and box and pan work alone, but will accommodate inside bending, radius forming many other intricate forming operations with special attachments. They are limited in versatility only by the operator's ingenuity. These brakes will form a 1" flange over the entire length in their rated capacity. Heavy duty springs reduce clamping effort and adjustable counterweights reduce bending effort. The upper beam may be moved directly to the rear either 6 or 8 inches to accommodate box fingers and special forming attachments. The normal maximum opening between the upper beam and the lower beam is 1.3/4 " and may be increased to 4" to accept box and pan fingers. When the apron angle iron work support is removed, brake capacity is reduced by 2 gauges. When the apron angle iron work support and apron filler plates are removed, brake capacity is reduced by 4 gauges. When both are removed , 1/4" reverse bends may be made except on 8 foot and 10 foot, 12 foot gauge brakes only 3/8" reverse bends may be made. When bending stainless steel brake capacity is reduced 4 gauges for both straight and finger bending. The Use Of Special And Standard

Blades : Caution : Do not form Wire, Nail, Rope or Pipe in these Brakes. Showing section of machine with standard bar and fingers. Note position of folding axis which is constant, no matter what bend is being formed. Metal is in position after a simple right angle bend. For this operation, making small radius bends, the folding beam is lowered in the side arms and the metal clamped in the normal way. When folding beam is raised, the gap between the nose of the folding blade and the face of the folding beam allows a rounded bend to be made. Showing how small return bends can be formed using a specially stepped bar. Such a bar is useful for moulding work. The folding beam lifts high enough to allow that part of the metal on the inside of the beam to be withdrawn over the bar. Narrow return bends can also be formed by substituting the narrow auxiliary blade supplied, for the angle blade, giving a smaller thickness to the folding beam.

Figure - 3 Brake will form a one inch flange at rated capacity its entire length with the Apron Filler Plate (101) and Apron Work Support (104) in place. (See fig. 3) Removal of Apron Work support (104), reduces brake capacity by 2 gauges. Removal of both Apron Work support (104) and the Apron Filler Plate (101) reduces brake capacity by 4 gauges. Figure - 4 Minimum Reverse Bends : Removal of both Apron Work support and the Apron Filler Plate permits 1/4" reverse bends to be made on all brakes except Models 8ft. x 10ft. On these two models the minimum reverse bend is 3/8" (See Fig. 4) Figure - 5 To Flatten Seam With Apron : Bend metal over brake nose to 45". Remove metal. Place against upper beam and flatten

Universal Combination bending brakes represent a modern departure from the old conventional hand brake design. They are not limited to straight bending and box and pan work alone, but will accommodate inside bending, radius forming many other intricate forming operations with special attachments. They are limited in versatility only by the operator's ingenuity.

These brakes will form a 1" flange over the entire length in their rated capacity. Heavy duty springs reduce clamping effort and adjustable counterweights reduce bending effort. The upper beam may be moved directly to the rear either 6 or 8 inches to accommodate box fingers and special forming attachments. The normal maximum opening between the upper beam and the lower beam is 1.3/4 " and may be increased to 4" to accept box and pan fingers. When the apron angle iron work support is removed, brake capacity is reduced by 2 gauges.

When the apron angle iron work support and apron filler plates are removed, brake capacity is reduced by 4 gauges. When both are removed , 1/4" reverse bends may be made except on 8 foot and 10 foot, 12 foot gauge brakes only 3/8" reverse bends may be made. When bending stainless steel brake capacity is reduced 4 gauges for both straight and finger bending.

Elab Engineering Equipments Manufacturers

© LAB ENGINEERING