

Product Name :
 Spot Weldeing

Product Code :
 wm0005



Description :

Spot Weldeing

Technical Specification :

Spot Weldeing.

	6	7	10	15	20	25	15	20	30																			
K																												
V	5																											
A																												
R																												
at																												
in																												
g																												
T	2	3	3	4	3	4	6	9	3	4	6	9	3	4	6	9	3	4	6	9								
hr	2.	0	0	0	0	6	0	0	0	6	0	0	0	6	0	0	0	6	0	0	0	6	0	0	0	6	0	0
o	5																											

at
D
e
p
t
h
:
(
c
m
)
T
h
r
o
a
t
C
l
e
a
r
a
n
c
e
:
(
c
m
)
W
e
l
d
i
n
g
M
.
S
h
e
e
t
M
a
x
2
X
m
m
R
a
n
g
e
t
h
i
c
k
n
e
s

20-30

20-30

20-30

1. 1. 2 1. 2. 2 1. 1 3. 3 2. 2 4 3. 3 2. 3. 3 2 1. 4 3. 3 2. 5 4. 4 3.
6 8 0. 9 5 0. 6 0 5 0. 5 0. 0. 5 0. 5 5 0. 0. 8 1. 6 0. 8 1. 5 0. 5
0. 0. 7 0. 0. 3 0. 0 0. 5 0. 5 7 0. 5 0. 0. 5 4 0. 0 0. 7 0. 2 1 9 0.
3 5 6 4 5 2 . 6 4 6 4 6 3 8 6 7
5 2

S
M
in
2
X
m
m
:

K
V
A
R
at
in
g

C
ur
re
nt
C
o
nt
ro
l:
C
l
a
s
s
of
In
s
ul
at
ion
:
C
o
ol
in
g
Tr
a
n
sf
or
m
er

WITH CERTAIN LIMITATIONS S. S. & BRASS CAN ALSO BE SPOT WELDED

4.	5.	7	10.5	14	17.5	10.5	14	21
2	2							
	5							

By means of tap change links between (approx.) 55% and 100%

F	F	F	F	F	F	F	F	F
---	---	---	---	---	---	---	---	---

AIR

WATER

:
C
o
o
l
i
n
g
A
r
m
s
&
El
e
ct
ro
d
e
s
:

WATER

WATER

CUSTOMERS TO PROVIDE FOLLOWING SERVICES

M 230 V.IPh. 415 Volts. Single phase, 50 Hz : (2 lines of 3 phase supply)
ai 50 Hz / or

n
s
s
u
p
pl
y
:

M 10 14 25 sq : mm 14 sq : mm 25 sq : mm
ai sq : mm
n mm
s

u
p
pl
y
c
a
bl
e
si
z
e
(c
o
p
p
er
) :

M 2 Pole - 2 Pole - 60 Amps 2 Pole - 100 Amps
ai 30

n amps.

Disconnection switch:
Action:
Fuse:
Water at maximum temperature of 30°C and

D 1 2 30
el 5 0 Amps
a A A

60 Amps

30 Amps

60 Amps

5 Ltrs Per minute

10 Ltrs Per minute

M
i
n
i
m
u
m
P
r
e
s
s
u
r
e
o
f
2.
1
K
g
f
/c

2 :

Ai
r :

5.6 kgf/cm²

5.6 kgf/cm²

 **LAB ENGINEERING**

Elab Engineering Equipments Manufacturers