

Product Name :
Heavy Duty Hydraulic Thread Rolling Machine**Product Code :**
bp0003**Description :**

Heavy Duty Hydraulic Thread Rolling Machine

Technical Specification :

Heavy Duty Hydraulic Thread Rolling Machine.

Heavy Duty Hydraulic Thread Rolling Machine.

The thread rolling is basically a cold-forging process that forms the entire length of an external thread by displacing the blank material. Threads are produced on the blanks of predetermined diameter by a rolling action under pressure and between two rotating cylindrical steel roll dies whose working faces are suitably threaded. This action plastically deforms the blank in such a manner that a portion of the blank metal is displaced to form the root of the thread and raised in unbroken fibre-flow lines to form the crest of the thread.

The roll dies rotate synchronously on parallel or slightly tilted horizontal spindle shafts that are adjustable by sliding laterally. The dies are made of special steel alloy with an exceptional hardness and toughness resulting in maximum wear resistance. The blank is placed on a carbide tipped work rest blade or center support disposed between the dies and after a complete cycle of approach, rolling and release of the hydraulically

operated

right hand spindle shaft the rolled thread is removed. The blank is placed in the rolling position, either by hand or automatically. A timer built into the machine release the hydraulic pressure on the roll dies when the required diameter is completed and returns the right hand spindle head to its starting position.

SPECIFICATIONS

Workpiece Diameter	Max. 24 MM	Max. 42 MM
Pitch	Max. 3 MM	Max. 5 MM
In-feed thread length	Max. 80 MM	Max. 150 MM
Through feed thread length	Max. 3000 MM	Max. 4000 MM
Rolling force infinitely adjustable	Max. 8 Ton	Max. 16 Ton
Rolling and idle time infinitely adjustable	Max. approx. 30-s	Max. approx. 30-s
Spindle axis swivel for through feed rolling	Max. 5	Max. 5
Spindle speed RPM	60/90	20/40/60
Main Motor	2.2 K.W.	3.7 K.W.
Hydraulic Motor	1.5 K.W.	2.2 K.W.
Spindle Diameter	40	54
Rolling Die Diameter	120	180
Weight of the machine	1000 kg apporx.	3200 kg apporx.
Standard electrical connection	415 V, 50 Hz, 3 ph.	415 V, 50 Hz, 3 ph.

 **LAB ENGINEERING**

Elab Engineering Equipments Manufacturers