

Product Name :
 VACUUM PUMPS

Product Code :
 SCIENTIFIC0013



Description :

VACUUM PUMPS

Technical Specification :

Vacuum pump single stage of sealed, air cooled, V-belt driven and mounted on base with ball guard etc. with motor 220 volts AC single phase

Displacement Limit: 32 Motor Single Phase 0.25
Displacement Limit: 50 Motor Single Phase 0.25
Displacement Limit: 74 Motor Single Phase 0.50
Displacement Limit: 100 Motor Single Phase 0.50
Displacement Limit: 32 Motor Single Phase 0.25
Displacement Limit: 50 Motor Single Phase 0.25
Displacement Limit: 74 Motor Single Phase 0.50
Displacement Limit: 100 Motor Single Phase 0.50
Accessories for Model S2019 and S2074
Vacuum gauge with regulator
Vacuum gauge with regulator and non-return valve combined
Vacuum bag with non-return valve and vacuum gauge with regulator combined
Vacuum without mercury range 10mm to 0.001 mmHg pressure
Vacuum with mercury
Size for above
22 mm
<small>Unit may vary with time. This specification is subject to change without notice. We reserve the right to alter the design without notice.</small>

Construction: Metal frame & panel is finished with a thick layer of epoxy based polyurethane paint which provides a strong highly scratch & chemical resistant surface. The panel is fitted with main indicator lamp, on/off pump switch, vacuum gauge with vacuum control valve. A thick wall stainless steel double support ring is provided in between the vacuum source & the vessel to be evacuated. A thick rubber mat is provided on the vacuum pump shaft to absorb vibration & noise & heavy castor wheels are in the bottom for easy mobility. To ease the support ring is fitted with fine strips of steel anti-slip.

Item safety sign: Not an anti vacuum pump for collection of toxic liquid

© LAB ENGINEERING

Elab Engineering Equipments Manufacturers