

**Product Name :**  
 B.o.d. Incubator

**Product Code :**  
 SCIENTIFIC0023



**Description :**

B.o.d. Incubator

**Technical Specification :**

B.O.D incubator are suitable for preservation of vaccines, fluids, liver extracts, chemicals etc. and to make biochemical oxygen demand determination.

Construction: The low temperature incubator is made of double walled 31.5 sheet finished with epoxy based powder coated paint, inner chamber is made of highly polished stainless steel/ anodized aluminium. Two doors are provided, inner door is made of transparent acrylic for inspecting specimens color door is insulated and is fitted with magnetic tape with lock and key. Temperature range from 5°C to 50°C with an accuracy of +1°C provided with two air circulating fans, high performance compressor, cooling coils, heating elements. Digital temperature control and display is also fitted with a door operated illumination and a castor wheel for easy mobility.

<p>CU FT. 0.1          Height mm: 325          Width mm: 325          Depth mm: 415</p> <p>Inner chamber: Aluminium</p>
<p>CU FT. 0.1          Height mm: 325          Width mm: 325          Depth mm: 415</p> <p>Inner chamber: SS</p>
<p>CU FT. 0          Height mm: 325          Width mm: 325          Depth mm: 330</p> <p>Inner chamber: Aluminium</p>
<p>CU FT. 0          Height mm: 325          Width mm: 325</p>

<p>Depth mm: 500</p> <p>Inner chamber: S.S</p>
<p>Cu.Ft.: 10 Height mm: 800 Width mm: 500 Depth mm: 500</p> <p>Inner chamber: Aluminium</p>
<p>Cu.Ft.: 10 Height mm: 800 Width mm: 500 Depth mm: 500</p> <p>Inner chamber: S.S</p>
<p>Cu.Ft.: 12 Height mm: 900 Width mm: 600 Depth mm: 580</p> <p>Inner chamber: Aluminium</p>
<p>Cu.Ft.: 12 Height mm: 900 Width mm: 600 Depth mm: 580</p> <p>Inner chamber: S.S</p>

 **LAB ENGINEERING**

**Elab Engineering Equipments Manufacturers**