© LAB ENGINEERING

Email:

purchase@elabengineeringequipments.com Phone: +91-9811375383

Product Name:

Digital Conductivity TDS and Meter

Product Code: ELABANALYTICAL0033

© LAB ENGINEERING

Description:

Digital Conductivity TDS and Meter

Technical Specification:

Extremely Useful for Water Analysis Highly Stable and Accurate High Sensitivity Range 3½ Digit Display

Digital Conductivity/TDS is extremely useful for fast and accurate determination of Total Dissolve Solids in liquid. A high content of dissolved solids elevates the density of water influences osmo-regulation of fresh water organisms and reduces solubility of gases thereby reducing the utility of water for drinking, irrigation and industrial purpose.

Therefore, determination of Total Dissolved Solids in one of the important parameter in water analysis

The use of solid stat technology and IC circuitry makes the instrument versatile and reliable.

The instrument is ideal for testing water, drinking water, waste water brine solution, sea water and soluble salts etc.

Range TDS: 0-200 ppm, 0-2 ppt, 0-20.00 ppt (20,000 ppm), 0-200 ppt (2,00,000 ppm) 0-1000 ppt (1 million ppm)

Range Cond: 200 uS, 2 mS, 20 mS, 200 mS, 2000 mS

Resolution: 0.1 ppm Accuracy: 1% FS ±1 digit

Cell constant: Adjustable with indication on Digital Display

Temperature Compensation: 0 to 500C

Resolution: 0.1 ppm

Cond/TDS Cell: Platinum DIP Type

Display: 31/2 Digit Seven Segment LED Display

Power: 230V±10%AC,50Hz

Accessories: Coductivity/TDS Cell, Operation Manual, Dust Cover

© LAB ENGINEERING

Elab Engineering Equipments Manufacturers

2/2