# **© LAB ENGINEERING**

Email: purchase@elabengineeringequipments.com

Phone: +91-9811375383

Product Name :	Product Code :
Digital Planimeter	CVEL0001

### **© LAB ENGINEERING**

#### **Description:**

Digital Planimeter

#### **Technical Specification:**

Placom Digital Planimeter KP-90N-Series with the most advanced functions and perfect reliability. The most standard model of "Koizuimi Placom" N-Series has made the excitingly highest attainment in the history of Placom Digital Planimeter KP-90N ever made. Measuring capacity is remarkably enlarged. Measuring by 6-digit pulse count enables to measure 100 times larger accumulative area than ordinary planimeters. Easy calculations of Cumulative and Average Value Measurement.

We are well-known manufacturers, OEM suppliers of Digital Planimeter for Civil Engineering Lab Equipments. Contact us for high quality Digital Planimeter for Civil Engineering Lab Equipments for schools lab, college lab, universities, research labs, various teaching and workshop training laboratories and industries in India.

Type	Roller Type		Polar Type	
	With Computing	Single Function	With Computing	Single Function
	Function		Function	
Display	Liquid Crystal, 8-digit Figures			
	13 Symbols	6 Symbols	13 Symbols	6 Symbols
Symbol	Batt-E, SCALE	Batt-E	Batt-E, SCALE	Batt-E
	Memo, Hold	Memo, Hold	Memo, Hold	Memo, Hold
	cm2, m2, km2, in2,	cm2, in2, etc.	cm2, m2, km2, in2,	cm2, in2, etc.

ft2, acre etc. ft2, acre etc.

Converting Function Unit and Scale value Unit(in2, cm2) Unit and Scale value Unit(in2, cm2)

Accumulated Maximum 10m2(Scale 1:1)

Measuring Value

Measuring Range Maximum vertical width: 325mm Maximum, with the pole put outside the

Horizntal roller rotating length: 30m pattern: 300mm in diameter

Maximum, with the pole put inside the

pattern: 800mm in diameter

Accuracy Within +/-0.2%(Within +/-2/1000pluses)

Power Supply

• Built-in NiCd Battery(rechargeable through AC Adapter)

• AC Adapter 100-240V (Auto-power-off function is provided.)

Operating Duration Approx. 30 hours of continuous operation

Battery Charging Approx. 15 hours

Time

Main Unit Weight 750g 780g

Accessories Supplied AC Adapter and Plastic Case

## **© LAB ENGINEERING**

**Elab Engineering Equipments Manufacturers** 

2/2