

Product Name :
Conductivity meter

Product Code :
EVR0004



Description :

Conductivity meter

Technical Specification :

MICROPROCESSOR CONDUCTIVITY / TDS / TEMP.

DISPLAY	16 X 2 Alpha Numeric LCD Display
RANGE	0.1 μ S to 100mS (6 Decadic Ranges)
RESOLUTION	0.01 μ S.
ACCURACY	\pm 1% of F.S. \pm 1 Digit
CALIBRATION	Auto / Manual.
TEMPERATURE COMP.	0 to 100 UC.
CELL CONSTANT	0.1 To 5.0 Adjustable.
SENSOR	Up to 100 Samples.
POWER	230V \pm 50 Hz. AC.

DELUXE DIGITAL CONDUCTIVITY METER

DISPLAY	3.5 Digit LED.
RANGE	5 Ranges, 0 to 1000Mhos / cm.
ACCURACY	\pm 1% of F.S. \pm 1 Digit.
TEMPERATURE COMP.	Auto / Manual 0 To 50 deg. C
CELL CONSTANT	Adjustable.
SENSOR	Conductivity Cell.
POWER	230V \pm 50 Hz AC.

DIGITAL CONDUCTIVITY METER

DISPLAY	3.5 Digit LED.
RANGE	5 Ranges, 0 to 1000Mhos / cm.
ACCURACY	± 1% of F.S. ± 1 Digit.
TEMPERATURE COMP.	Manual 0 To 50 deg. C
CELL CONSTANT	Adjustable.
SENSOR	Conductivity Cell.
POWER	230V ± 50 Hz AC.

 **LAB ENGINEERING**

Elab Engineering Equipments Manufacturers