© LAB ENGINEERING

Email:

purchase@elabengineeringequipments.com Phone: +91-9811375383

Product Name : PH/MV/Temperature Meter

Product Code: ELAB-ELC0006

© LAB ENGINEERING

Description:

PH/MV/Temperature Meter

Technical Specification:

pH/mV/Temperature Meter

Features:-

Microprocessor Based

Water Proofing

Floats on Water

Large LCD Display

Automatic Temperature Compensation (ATC)

Data Hold, Max/Min and °C/ °F switchable

Low Battery and Consumption Indicator

Auto Power-Off after 10 minutes

pH/Conductivity/TDS/Salt/Temp

Waterproof Tester is a microprocessor based tester used to determine pH, mV, Temperature in a liquid.

This tester has wide applications in agriculture, anti-freeze recycling, aquarium, boiler, chemical industry, cooling tower, drinking water, fish farming, food industry, garden husbandry, hydroponics, laboratory usage, plating industry, swimming pool & spa, water treatment etc.

It has rugged design for field use.

It floats on water. It has Automatic Temperature Compensation (ATC) and is degree °C/°F switchable. It displays Maximum/Minimum value and data hold on large LCD display. It has low battery and consumption indicator along with auto shut off after 10 minutes of non use.

Specifications:-

Display	Large LCD to display respective
	parameters,
	Battery level, ATC and Temperature
Range	pH: -2 - 16.00
	mV: -1000 - 1000 mV
Temp	0 - 90.0 °C
Resolution	pH: 0.01 pH, mV: 1 mV, Temp.: 0.1 °C
Accuracy	pH: ± 0.01 +1 Digit, mV: ±2 +1 Digit,
	Temp: ± 0.2 °C +1 Digit
Temperature Compensation	Automatic Temperature Compensation
	(ATC)
	with temperature display
Temperature Coefficient	2% per °C
Water Proof	As per IP 57 water proofing standard
Calibration	pH: 4.00, 7.00 and 10.01
Power	DC 1.5 V x 4 battery (UM-4/AAA)
	Auto Power off after 10 minutes
Dimensions	Meter: 195 x 40 x 36 mm
	Kit: 230 x 205 x 50 mm
Weight	Meter: 135 g with battery (Approx.)
	Kit: 780 g (Approx.)
Others Features	Auto Power-off after 10 minutes, Hold
	function to freeze reading, Push button
	calibration, Water-proof IP-57,
	Temperature coefficient - 2% per °C, Self-
	Diagnostics message for low battery
ACCESSORIES	Standard Calibration Solution (50 ml),
	Battery, Lanyard, Operation Manual and
	Carrying Case

© LAB ENGINEERING

Elab Engineering Equipments Manufacturers