

**Product Name :**  
Computerized Stefan Boltzman Apparatus**Product Code :**  
HEMT0006 LAB ENGINEERING**Description :**

Computerized Stefan Boltzman Apparatus

**Technical Specification :**

The heat transfer trainer enables users to match the individual heat quantities to the corresponding type of transfer.

The core element is a heated metal cylinder located at the center of the pressure vessel.

The surface temperature of the heated metal cylinder is controlled.

Temperature sensors measure the surface temperature of the metal cylinder and the wall temperature of the pressure vessel.

In addition to the heating power of the metal cylinder, it is possible to study the heat transport from the metal cylinder to the wall of the pressure vessel.

The pressure vessel can be put under vacuum or positive gauge pressure.

In the vacuum, heat is transported primarily by radiation.

If the vessel is filled with gas and is under positive gauge pressure, heat is also transferred by convection.

It is possible to compare the heat transfer in different gases.

In addition to air, nitrogen, helium, carbon dioxide or other gases are also suitable.

A rotary vane pump generates negative pressures down to approx. 0,02mbar.

Positive gauge pressures up to approx. 1bar can be realized with compressed air.

Two pressure sensors with suitable measuring ranges are available for the pressure measurement: a Pirani sensor measures the negative pressure while a piezo-resistive sensor measures the positive pressure.

The measured values can be read on digital displays.

At the same time, the measured values can also be transmitted directly to a PC via USB, where they can be analyzed with the software.

---

#### FEATURES:

Experiments in vacuum  
Heat transfer by radiation  
Determination of the radiation coefficient  
Determination of the heat quantity transferred by convection  
Determination of the heat transfer coefficient based on measured values  
Experiments at ambient pressure or positive gauge pressure  
Heat transfer by convection and radiation  
Theoretical determination of the heat transfer coefficient based on the Nusselt number  
Comparison of the heat transfer in different gases  
Heat transport between heating element and vessel wall by convection and radiation  
Heating element

#### SPECIFICATION:

Pump for vacuum generation  
Power consumption: 250W  
Nominal suction capacity: 5m<sup>3</sup>/h  
Final pressure with gas ballast: 3\*10<sup>-3</sup>mbar  
Final pressure without gas ballast: 3\*10<sup>-3</sup>mbar  
Output: 20W  
Radiation surface area: approx. 61cm<sup>2</sup>  
Pressure vessel :  
Pressure: -1...1,5bar  
Volume: 11L  
Measuring ranges :  
Negative pressure: 0,5\*10<sup>-3</sup>...1000mbar  
Pressure: -1...1,5bar rel.  
Temperature: 0...250°C  
Power: 0...23W  
Required for Operation :  
230V, 50Hz, 1 phase  
230V, 60Hz, 1 phase; 120V, 60Hz, 1 phase

 **LAB ENGINEERING**

**Elab Engineering Equipments Manufacturers**